

Cu ropes

Bare copper conductors

Standard: ČSN 34 7201 (IEC 228)

Usage:

The conductors are intended for connections of locations of equal electrical potential or for high currents and low voltages.



Nominal cross section (mm ²)	Max. conductor resistance (Ω/km)	Outer diameter (mm) ca.	Metal weight (kg/km)	Standard lengths/packing (m)
Cu solid conductor for fixed installation (IEC 228 class 1)				
0.5	36.00	0.8	5	1000 Sp
0.75	24.50	1.0	7	1000 Sp
1	18.10	1.1	10	1000 Sp
1.5	12.10	1.4	15	1000 Sp
2.5	7.41	1.8	25	1000 Sp
4	4.61	2.2	39	1000 Sp
6	3.08	2.7	59	1000 Sp
10	1.83	3.5	98	1000 T
16	1.15	4.4	157	1000 T

Nominal cross section (mm ²)	Minimum number of wires in conductor	Max. conductor resistance (Ω/km)	Outer diameter (mm) ca.	Metal weight (kg/km)	Standard lengths/packing (m)
Cu stranded conductor for fixed installation (IEC 228 class 2)					
1.5	7	12.1000	1.6	15	1000 Sp
2.5	7	7.4100	2.0	25	1000 Sp
4	7	4.6100	2.6	39	1000 Sp
6	7	3.0800	2.9	59	1000 T
10	7	1.8300	3.7	98	1000 T
16	7	1.1500	4.7	157	1000 T
25	7	0.7270	6.0	245	1000 T
35	7	0.5240	6.9	343	1000 T
50	7	0.3870	8.2	490	1000 T
70	19	0.2680	9.8	686	1000 T
95	19	0.1930	11.6	931	500 T
120	19	0.1530	13.1	1,176	500 T
150	19	0.1240	14.4	1,470	500 T

Cu ropes

Nominal cross section (mm ²)	Minimum number of wires in conductor	Max. conductor resistance (Ω/km)	Outer diameter (mm) ca.	Metal weight (kg/km)	Standard lengths/ packing (m)
Cu stranded conductor for fixed installation (IEC 228 class 2)					
185	37	0.0991	16.2	1,813	250 T
240	37	0.0754	18.7	2,352	250 T
300	37	0.0601	21.1	2,940	250 T
400	61	0.0470	24.3	3,920	200 T
500	61	0.0366	27.2	4,900	200 T
630	61	0.0283	30.9	6,174	200 T

Nominal cross section (mm ²)	Maximum diameter of wires in conductor (mm)	Max. conductor resistance (Ω/km)	Outer diameter (mm) ca.	Metal weight (kg/km)	Standard lengths/ packing (m)
Cu stranded conductor for movable installation (IEC 228 class 5)					
0.5	0.21	39.0000	1.0	5	1000 Sp
0.75	0.21	26.0000	1.1	7	1000 Sp
1	0.21	19.5000	1.3	10	1000 Sp
1.5	0.26	13.3000	1.6	15	1000 Sp
2.5	0.26	7.9800	2.0	25	1000 Sp
4	0.31	4.9500	2.5	39	1000 Sp
6	0.31	3.3000	3.2	59	1000 T
10	0.41	1.9100	4.8	98	1000 T
16	0.41	1.2100	5.5	157	1000 T
25	0.41	0.7800	7.2	245	1000 T
35	0.41	0.5540	8.4	343	1000 T
50	0.41	0.3860	10.2	490	1000 T
70	0.51	0.2720	12.8	686	1000 T
95	0.51	0.2060	14.0	931	500 T
120	0.51	0.1610	16.0	1,176	500 T
150	0.51	0.1290	17.9	1,470	250 T
185	0.51	0.1060	19.6	1,813	250 T
240	0.51	0.0801	22.8	2,352	250 T

Cu ropes

Nominal cross section (mm ²)	Maximum diameter of wires in conductor (mm)	Max. conductor resistance (Ω/km)	Outer diameter (mm) ca.	Metal weight (kg/km)	Standard lengths/ packing (m)
Cu stranded conductor for high movable installation (IEC 228 class 6)					
0.5	0.16	39.0000	0.9	5	1000 Sp
0.75	0.16	26.0000	1.1	7	1000 Sp
1	0.16	19.5000	1.2	10	1000 Sp
1.5	0.16	13.3000	1.5	15	1000 Sp
2.5	0.16	7.9800	1.6	25	1000 Sp
4	0.16	4.9500	2.5	39	1000 Sp
6	0.21	3.3000	3.6	59	1000 T
10	0.21	1.9100	5.0	98	1000 T
16	0.21	1.2100	6.0	157	1000 T
25	0.21	0.7800	7.5	245	1000 T
35	0.21	0.5540	8.8	343	1000 T
50	0.31	0.3860	10.5	490	1000 T
70	0.31	0.2720	12.5	686	1000 T
95	0.31	0.2060	14.7	931	500 T
120	0.31	0.1610	17.1	1,176	500 T
150	0.41	0.1290	18.3	1,470	250 T
185	0.41	0.1060	19.9	1,813	250 T
240	0.41	0.0801	22.5	2,352	250 T

Subject to technical changes.

Cu braids

Bare copper braids

Standard: TP PRAKAB 11/02

Usage:

The conductors are intended for movable connections of electrical equipment in dry premises free of aggressive gases.



Construction:

- 1 Cu fine wires stranded into strands, strands into braids not flattened (round) and flattened (flat).

Nominal cross section (mm ²)	Max. conductor resistance (Ω/km)	Outer diameter not flattened conductor (mm) ca.	Width of flattened conductor (mm) ca.	Thickness of flattened conductor (mm) ca.	Metal weight (kg/km)	Standard lengths/packing (m)
Braid of Cu fine wires Ø 0.071 mm						
6	2.87	5.0	8.5	0.9	59	50 R
10	1.72	7.0	11.5	1.2	98	50 R
16	1.08	8.5	15.2	1.4	157	50 R
20	0.86	10.0	16.8	1.7	196	50 R
25	0.69	11.0	19.0	1.9	245	50 R
35	0.49	13.5	21.5	2.4	343	50 R
Braid of Cu fine wires Ø 0.100 mm						
10	1.72	7.0	11.2	1.3	98	50 R
16	1.08	8.5	15.5	1.5	157	50 R
25	0.69	11.0	20.0	2.0	245	50 R
35	0.49	13.5	24.0	2.2	343	50 R
50	0.34	17.0	28.5	2.8	490	50 R
Braid of Cu fine wires Ø 0.200 mm						
25	0.69	11.0	22.0	1.6	245	50 R
35	0.49	13.5	24.5	2.4	343	50 R
50	0.34	17.0	31.0	2.7	490	50 R
70	0.25	20.0	35.0	3.8	686	50 R

Subject to technical changes.