

A-2Y(L)2YV

Signalling cable, screened

DESIGN



- 1 | Copper conductor, round solid (RE)
- 2 | Core insulation (PE), cores star quaded, quads stranded in concentric layers
- 3 | Inner covering (plastic tape)
- 4 | Screen (plastic laminated aluminium foil, which is welded to the PE sheath + drain wire)
- 5 | Sheath (PE black, increased thickness, UV resistant)

TECHNICAL DATA

- Standard:**
DB AG No.: 416.0115
- Test voltage:**
Core-core: 2,500 VAC
- Temperature range:**
laying temperature: min. -10 °C
operating temperature: -40°C up to +60°C
- Bending radius (min.):**
multiple bending: 20 x Ø of cable
single bend: 10 x Ø of cable
- Core identification:**
DB AG No.: 416.0116
- Certificate:**
VDE Germany

APPLICATION

For general use as a underground cable in signalling devices.

ELECTRICAL PARAMETERS

Conductor diameter		(mm)	0.90	1.40
Loop resistance, max.		(Ω/km)	56.6	23.4
Insulation resistance, min.		(MΩ.km)	10,000	10,000
Mutual capacitance at 800 Hz, max.		(nF/km)	45	45
Capacitance unbalances at 800 Hz				
k_1 max. 100% of values		(pF/500 m)	650.0	650.0
k_1 max. 50% of values		(pF/500 m)	150.0	-
k_{9-12} max., immediately adjacent quads	100% of values	(pF/500 m)	500.0	500.0
k_{9-12} max., immediately adjacent quads	50% of values	(pF/500 m)	150.0	-
k_{9-12} max., remote quads resp. quads in different layers	100% of values	(pF/500 m)	150.0	150.0
$e_{1/2}$ and $e_{a1/2}$ max.	100% of values	(pF/500 m)	1,300.0	1,300.0
Far-end crosstalk attenuation at 90 kHz, min.	100% of line circuits	(dB/1,000 m)	58.0	33.0
Far-end crosstalk attenuation at 90 kHz, min.	80% of line circuits	(dB/1,000 m)	62.0	-
Wave attenuation at 90 kHz, max.		(dB/1,000 m)	3.3	2.6

A-2Y(L)2YV

Number of quads x conductor diameter (mm)	Outer diameter (mm) ca.	Total weight (kg/km) ca.	Standard lengths/packing (m)
A-2Y(L)2YV			
1 x 4 x 0.9	10.0	120	1,000 D
3 x 4 x 0.9	15.0	220	1,000 D
5 x 4 x 0.9	17.0	330	1,000 D
7 x 4 x 0.9	19.0	410	1,000 D
10 x 4 x 0.9	22.0	560	1,000 D
14 x 4 x 0.9	25.0	730	1,000 D
20 x 4 x 0.9	28.0	980	1,000 D
30 x 4 x 0.9	34.0	1,410	1,000 D
40 x 4 x 0.9	38.0	1,820	1,000 D
1 x 4 x 1.4	12.0	170	1,000 D
3 x 4 x 1.4	19.0	410	1,000 D
5 x 4 x 1.4	22.0	620	1,000 D
7 x 4 x 1.4	24.0	800	1,000 D
10 x 4 x 1.4	29.0	1,090	1,000 D
14 x 4 x 1.4	33.0	1,490	1,000 D
20 x 4 x 1.4	39.0	2,040	1,000 D
30 x 4 x 1.4	46.0	2,950	1,000 D
40 x 4 x 1.4	53.0	3,900	500 D

Subject to technical changes.