



PRAKAB PRAŽSKÁ KABELOVNA

## Cable support construction for cable systems with integrated function E30



Producer	Cable support construction	Support distance (m)	Width/ Diameter (mm)	Side height (mm)	Plate thickness (mm)	Max. load (kg/m)	Type	Bracket	Support	Max levels	(N)HXH FE180/E30		(N)HXCH FE180/E30		JE-H(St)H FE180/E30-E90	
											Dimension range	ABP	Dimension range	ABP	Dimension range	ABP
<b>Standard constructions</b>	Single clip	0.3									✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	✓	P-MPA-E-09-016
	Single clip with support	0.6									✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	✓	P-MPA-E-09-016
	Cable ladder	1.2	400	60	1.5	20					✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	✓	P-MPA-E-09-016
	Cable tray	1.2	300	60	1.5	10					✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	✓	P-MPA-E-09-016
<b>OBO Bettermann</b>	Collecting clamp	0.6				1.1	2031/M15				n x ≥16mm <sup>2</sup>	P-MPA-E-09-016	x	-	x	-
	Collecting clamp – ceiling installation	0.5				1.1	GRIP 2031/M15				1.5mm <sup>2</sup>	P-1016 DMT DO	x	-	x	-
	Collecting clamp – ceiling installation	0.5				2.5	GRIP 2031/M30				x	-	x	-	✓	P-1016 DMT DO
	Single clip	0.8					732				✓	P-MPA-E-09-016	x	-	x	-
	Single clips with boxes	0.6					FireBox B 100E		Profile rail "C" 1268/SL, clip 732		n x ≥6mm <sup>2</sup>	P-MPA-E-09-016	x	-	x	-
	Single clips with boxes	0.6					FireBox B 250E		Profile rail "C" 1268/SL, clip 732		n x ≥16mm <sup>2</sup>	P-MPA-E-09-016	x	-	x	-
	Metal tube	1.2	63			3.3	ES 63, Filling factor 60%				✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	x	-
<b>NIEDAX</b>	Cable tray	1.5	300	60	0.75	20	RLVC 60.300 S	KTA 300	HU 5050	3	✓	P-1016 DMT DO	✓	P-1016 DMT DO	x	-
	Cable tray	1.5	400	60	0.9	30	RLVC 60.400 S	KTA 400	HU 5050	2	✓	P-1016 DMT DO	✓	P-1016 DMT DO	✓	P-1016 DMT DO
	Collecting clamp – wall installation	0.6				3	SHS 30		SHSEW 30		✓	P-MPA-E-09-016	x	-	✓	P-MPA-E-09-016
	Collecting clamp – ceiling installation	0.6				3	SHS 30		SHSEW 30		✓	P-MPA-E-09-016	x	-	✓	P-MPA-E-09-016
<b>PUK</b>	Cable tray	1.25	500	60	1.5	20	RGS 60-50S	KUM-BS 050F	KDU 50-07F	2	✓	P-MPA-E-09-016	x	-	x	-
<b>STUDER</b>	Collecting clamp	0.8				4.9	BETAFIXss				✓	P-MPA-E-09-016	✓	P-MPA-E-09-016	x	-
<b>LANZ</b>	Cable tray on support	1.5	100	50	wire ø 4	10	G-Kanal 50 x 100		G-Stiel	2	1.5mm <sup>2</sup>	P-1016 DMT DO	x	-	✓	P-1016 DMT DO
	Cable tray – ceiling installation	1.5	150	100	wire ø 4	10	G-Kanal 100 x 150		Klemmplatte		1.5mm <sup>2</sup>	P-1016 DMT DO	x	-	x	-
	Installation duct – wall installation	0.8				0.75	C-kanal				1.5mm <sup>2</sup> – 2.5mm <sup>2</sup>	P-1016 DMT DO	x	-	x	-
	Cable ladder – wall installation	1.8	400	60	1.25	20	WSP-Multibahn 400 x 60	Schwerlast-konsole	wandmontage		x	-	x	-	✓	P-1016 DMT DO
	Cable ladder – ceiling installation	1.8	400	60	1.25	20	WSP-Multibahn 400 x 60	Multifix-Pro-filschiene 50 x 50	Deckenstütz Multifix + Tragbügel		x	-	x	-	✓	P-1016 DMT DO

Note: ✓ = all dimensions x = not offered